

Vac-Tron Equipment

The Industry Innovator



Standard Features

- 150 gallon/1 cubic yard debris tank with hydraulic tilt
- Full open rear door with manual wheel locking system
- 3" Portal shut-off inside of Vacuum tank
- 25 HP Kohler Gas Engine and optional 24 HP diesel engine

Vacuum Pump

- Positive displacement design rated at 550 cfm for gas and 580 cfm for diesel
- Capable of drawing 13" of Mercury
- Shaft and lobes manufactured as a single piece of steel (no key-way)

Filtration

- Filter System (wet or dry)
- Filtration cartridge for wet & dry applications that is removable & washable
- 44 sq ft filtration media, combined with 10-gallon water trap
- Wet or Dry industrial filter rated at 5:1 cloth ration and grain loading of 30-g/acf using 0.5 micron silica dust emissions of .0060 g/acf (filters down to 0.5 micron)



Water System

- 3000 psi @ 4 gpm high pressure water system
- Belt driven water pump with electric clutch with on/off control and low water auto shut-down
- 40 gallon water capacity
- 50' of high pressure hose rated at 4000 psi
- Hose reel mounted to trailer
- 5' roto wand with control handle
- 3' variable nozzle wand with control handle for clean up

Optional Trailer

- Torsion axle rated @ 3,500 lb with electric brakes
- Pintle hitch
- Jack stand with side cranks handle
- Under coated to prevent corrosion